

SWINGING FULL LENGTH DOORS



BT70SD

FEATURES

- Top-mounted condensing unit supplied with quick connects and an attractive cover.
- Automatic condensate evaporator standard on top mounted model.
- All remotes equipped with expansion valves - Specify refrigerant when ordering.
- Rigid all welded exterior with powder coat finish.
- Back annodized aluminum, self-closing swinging doors with heated frames and jambs.
- Double paned tempered insulated glass.
- Switch-controlled vertical LED lamps.
- Adjustable heavy duty white epoxy wire shelves with front product stop.
- Stainless steel floor.
- Environmentally friendly refrigerants.

REMOTE	BR52SD	BR70SD	BR79SD	BR103SD
Width	54"	70"	79½"	103"
Depth	31"	31"	31"	31"
Height	74 ½"	74 ½"	74 ½"	74 ½"
Volume/cu. ft.	51	70	77	103
Doors	2	2	3	4
Door Size	23" X 66"	31" X 66"	23" X 66"	23" X 66"
Shelves	10	10	15	20
Unit HP req'd	½	½	½ +	¾
Voltage	115	115	115	115
Amps	4	5	5	6
Lights	3	3	4	5
Shipping Weight	560#	700#	800#	1000#

TOP MOUNTED	BT52SD	BT70SD	BT79SD	BT103SD
Height w/ Cond Unit	90 ½"	90 ½"	90 ½"	90 ½"
Height W/ out Cond Unit	74 ½"	74 ½"	74 ½"	74 ½"
Voltage-top mounted	115	115	115	230/115
Amps top mounted	12	13	16	15



105 Steamboat Drive • Warminster, PA 18974
 Phone (215) 675-9220 • (800) 673-7868 • Fax (215) 675-0878
 Website: powersequipment.com • Email: sales@powersequipment.com